

Declaration of Performance

2 layer Optima wood-alu



DoP ref. Opt2022-A2-1

The performance of the product is in conformaty with the declared performance.

The declaration of performance is issued under the responsibility of JABS Group A/S.

Product type: Windows and external pedestrian doorset

Identification: 2 layer Optima wood-alu

Intended use: Dedicated for use in residential and public buildings

Manufacturer: JABS Group A/S, Cortex Park Vest 3
DK,5230 Odense M, Denmark
phone +45 70201887, e-mail info@jabsgroup.com

The Assessment and Verification of Constasy of Performance (AVCP): System 3

Harmonized standard & Notified Body: EN 14351-1:2006 A2 -2016
Windows and doors - Product standard,
Performance characteristics -
Part 1: windows and external pedestrian doorset

Danish Technological Institute, NB 1235 - Calculation of thermal properties: ITC report 130274
- Load bearing capacity of safety devices: Report 129215

Declared performance:

Resistance to wind load:	npd
Watertightness:	npd
Dangerous substances:	npd
Load bearing capacity of safety devices:	Passed
Acoustic performance:	npd
Thermal transmittance (U-value):	
- Window 1230x1480 mm standard glazing:	1,37
- Door outward opening 1230x2180 mm standard glazing:	1,40
Radiation properties:	
- Solar factor (gg-value):	0,73
- Light transmittance (LTg-value):	0,82
Air permeability:	npd

On behalf of the producer:

Bo Overgaard Christensen
Managing Director

Odense, 2024-08-20



JABS Group A/S
Cortex Park Vest 3
DK,5230 Odense M
Denmark

22

DoP ref. Opt2022-A2-1

EN 14351-1:2006 + A2:2016
NB 1235

Windows and external pedestrian doorset - Type: 2 layer Optima wood-alu

Dedicated for use in residential and public buildings

Resistance to wind load:	npd
Watertightness:	npd
Dangerous substances:	npd
Load bearing capacity of safety devices (reversible window):	Passed
Acoustic performance:	npd

Thermal transmittance (U-value):	
- Window outward opening 1230x1480 mm standard glazing:	1,37
- Door outward opening 1230x2180 mm standard glazing:	1,40

Radiation properties:	
- Solar factor (gg-value):	0,73
- Light transmittance (LTg-value):	0,82

Air permeability:	npd
-------------------	-----

npd: no performance determined

The actual values can be informed by contacting JABS Group A/S tlf.+45 70201887
acc. EN 14351-1:2006+A2:2016, Table E.1 note c. and Table E.2 note d.